





▼产品描述 Product Description:

型号 TYPE xx=V _{DRM} /100	I _{RSM} @T _C =70°C	V _{DRM}	I _{TSM} @T _{VJM} &10ms	V _{TM} @I _{TM} &T _C =T _{VJM}		V _{GT}	I _{GT}	T _{VJM}	R _{thCH}	F ±10%	外形 Fig
	A	V	kA	A	V	V	mA	°C	K/W	kN	
KS200-xx	200A	500-1800V	2.3	600	1.9	0.8-2.5	20-200	125	0.065	5	KS1
KS300-xx	300A	500-1800V	2.5	900	2.0	0.8-2.5	20-200	125	0.065	15	KS1
KS400-xx	400A	500-1800V	4.1	1200	2.3	0.8-2.5	20-200	125	0.045	15	KS2
KS500-xx	500A	500-1800V	4.2	1500	2.3	0.8-3	20-300	125	0.036	5	KS2
KS600-xx	600A	500-1800V	4.6	1800	2.5	0.8-3.5	20-400	125	0.036	10	KS3
KS800-xx	800A	500-1800V	6.8	2400	2.5	0.8-3.5	20-400	125	0.032	15	KS3



▼外形尺寸 Dimensions



KS1 图



KS2 图



KS3 图

